



# UNILENE

RESINA HIDROCARBÔNICA

SÉRIE	TIPO	APLICAÇÃO	PONTO DE AMOLECIMENTO (RB ° C)	COR GARDNER	ÍNDICE DE ACIDEZ
SÉRIE A	A-80	Indústria de borracha, adesivos, plásticos, cura de concreto, indústria da madeira, indústria de cartonagem, mastiques e componentes de asfaltos.	75-86	7 MAX.	< 0,10
	A-90		87-95	7 MAX.	< 0,10
	A-100		96-105	6 MAX.	< 0,10
SÉRIE B	B-100	Tintas, vernizes, hot-melt, plásticos.	95-105	6 MAX.	< 0,10
	B-110		106-115	6 MAX.	< 0,10
	B-120		116-125	6 MAX.	< 0,10
SÉRIE BS	BS-130	Adesivos, tintas de impressão.	126-135	5 MAX.	< 0,10
	BS-140		136-145	5 MAX.	< 0,10



# UNILENE

HYDROCARBON RESIN

SERIE	TYPE	USE	SOFTENING POINT (RB ° C)	COLOR GARDNER	ACIDITY INDEX
SERIE A	A-80	Rubber industry, adhesives, plastic modification, concrete curing, mastics and asphalt components, cardboard, wood industry.	75-86	7 MAX.	< 0,10
	A-90		87-95	7 MAX.	< 0,10
	A-100		96-105	6 MAX.	< 0,10
SERIE B	B-100	Paints, coatings, varnishes, epoxy systems, hot-melt, plastic modification.	95-105	6 MAX.	< 0,10
	B-110		106-115	6 MAX.	< 0,10
	B-120		116-125	6 MAX.	< 0,10
SERIE BS	BS-130	Adhesives, printing inks.	126-135	5 MAX.	< 0,10
	BS-140		136-145	5 MAX.	< 0,10

Products may have their specifications changed without previous notice, as well as productions may be discontinued.

For updated information and data sheets, please go to [www.quattor.com.br](http://www.quattor.com.br).